

PRO-TEC PREMIUM SL 20W-50

Description/Application/Properties

SAE 20W-50 is a mild alloyed, mineral engine oil specially designed to meet the requirements of classic vehicles and motorcycles with oil filters. The selected base oils and additives ensure optimum lubrication and very good wear protection under all operating conditions.

SL 20W-50 can be used in all operating conditions (City traffic, Road, Motorways), whatever the season.

Customer Benefits

Manufacturers standards, Resistance to oxidation, Engine protection and Cleanliness,
High viscosity index and an excellent viscosity stability.

Specification/Recommendation

Meets the Requirements of:

API SL/CF, ACEA A3/B3-04

MB 229.1, VW 505 00

Recommended for previous vehicles engines technology:

Peugeot, Renault, Toyota, Hyundai and Kia

TEST	UNIT	TEST METHOD	RESULT
VISCOSITY GRADE	-	SAE 300	20 W 50
DENSITY AT 15°C	kg/m ³	ASTM D 4052	891
VISCOSITY AT 40°C	mm ² /s	ASTM D 445	163.3
VISCOSITY AT 100°C	mm ² /s	ASTM D 445	18.1
VISCOSITY INDEX	-	ASTM D 2270	125
FLASH POINT	°C	ASTM D 92	245
POUR POINT	°C	ASTM D 97	-27

Unsere technischen Informationen stützen sich auf sorgfältige Untersuchungen und wurden nach dem neuesten Stand zusammengestellt. Dennoch kann sie nur unverbindlich beraten, da Anwendung und Verarbeitungsmethoden nicht in unserem Einfluss liegen. Keine Haftung für Druckfehler. Technische Änderungen vorbehalten.

Our information is based on careful examination and may be considered as reliable. However, all information supplied is a non-binding advise. No liability for printing errors, technical modifications and errors excepted.